

Cleveland State University

EngagedScholarship@CSU

---

Undergraduate Research Posters 2014

Undergraduate Research Posters

---

9-4-2014

## An Autonomous Robotic Indoor Environment Surveillance System

Andrew Gunnerson

*Cleveland State University*

Bogdan Olar

*Cleveland State University*

Haodong Wang

*Cleveland State University, H.WANG96@csuohio.edu*

Follow this and additional works at: [https://engagedscholarship.csuohio.edu/u\\_poster\\_2014](https://engagedscholarship.csuohio.edu/u_poster_2014)



Part of the [Robotics Commons](#)

**How does access to this work benefit you? Let us know!**

---

### Recommended Citation

Gunnerson, Andrew; Olar, Bogdan; and Wang, Haodong, "An Autonomous Robotic Indoor Environment Surveillance System" (2014). *Undergraduate Research Posters 2014*. 15.

[https://engagedscholarship.csuohio.edu/u\\_poster\\_2014/15](https://engagedscholarship.csuohio.edu/u_poster_2014/15)

This Article is brought to you for free and open access by the Undergraduate Research Posters at EngagedScholarship@CSU. It has been accepted for inclusion in Undergraduate Research Posters 2014 by an authorized administrator of EngagedScholarship@CSU. For more information, please contact [library.es@csuohio.edu](mailto:library.es@csuohio.edu).



# ***An Autonomous Robotic Indoor Environment Surveillance System***

Monte Ahuja College of Business

**Student Researchers:** Andrew Gunnerson and Bogdan Olar

**Faculty Advisor:** Haodong Wang

## **Abstract**

We developed an autonomous mobile robot platform capable of following a path and gather environmental data, including temperature, humidity, light intensity, etc. The robot is capable of detecting the path using its camera and correct most navigational errors, while the sensors support a limited set of instructions regarding which sensor data to collect and how often. Our experiment consisted of having the robot follow a looped path we set up in BU004 Lab. The robot was able to complete the loop and gather sensor data for light intensity, humidity and temperature at a frequency of once per second, and also positional data provided by the robot at around the same frequency.