1996

A New Pre-loaded Membrane Geometric Stiffness Matrix with Full Rigid Body Capabilities

Paul A. Bosela

Cleveland State University, p.bosela@csuohio.edu

D. R. Ludwiczak

NASA Lewis Research Center

Follow this and additional works at: https://engagedscholarship.csuohio.edu/encee_facpub

Part of the [Structures and Materials Commons](#)

[How does access to this work benefit you? Let us know!](#)

Publisher's Statement

NOTICE: this is the author's version of a work that was accepted for publication in Computers & Structures. Changes resulting from the publishing process, such as peer review, editing, corrections, structural formatting, and other quality control mechanisms may not be reflected in this document. Changes may have been made to this work since it was submitted for publication. A definitive version was subsequently published in Computers & Structures, 60, 1, (01-01-1996); 10.1016/0045-7949(95)60341-7

Original Citation

Bosela P. A., and Ludwiczak D. R. (1996). A New Pre-loaded Membrane Geometric Stiffness Matrix with Full Rigid Body Capabilities. Computers & Structures, 60, 1, 159-168.

This Article is brought to you for free and open access by the Civil and Environmental Engineering at EngagedScholarship@CSU. It has been accepted for inclusion in Civil and Environmental Engineering Faculty Publications by an authorized administrator of EngagedScholarship@CSU. For more information, please contact library.es@csuohio.edu.

A NEW PRE-LOADED MEMBRANE GEOMETRIC STIFFNESS MATRIX WITH FULL RIGID BODY CAPABILITIES

P. A. Bosela† and D. R. Ludwiczak‡

†Department of Engineering Technology, Cleveland State University, Cleveland, Ohio 44115, U.S.A.

‡Engineering Directorate, Structural Systems Division, Dynamics Branch,
NASA Lewis Research Center, Cleveland, Ohio 44135, U.S.A.

NOTATION

a	membrane element length
b	membrane element width
$[DFC]$	directed force correction matrix
$[DFC\text{Total}]$	matrix of all corrections ($[DFC] + [MCOR]$)
E	Young's modulus (Modulus of elasticity)
h	element thickness
$[Ke]$	elastic stiffness matrix
$[Kg]$	geometric stiffness matrix
K_{ij}	i, j element of stiffness matrix
$[M]$	mass matrix
$[MCOR]$	fixed end moment correction
N	distributed tensile load ($N_x = N$ for example, where $N_y = N_{xy} = 0$.)
N_x	distributed tensile load in x -direction
N_y	distributed tensile load in y -direction
N_{xy}	distributed shear load on membrane
α_e	element constant
β_e	element constant
ρ	mass density
ν	Poisson's ratio

INTRODUCTION

Due to economic constraints associated with payload cost, space structures must consist of light-weight, and subsequently relatively flexible, components. The total stiffness of a member, in many cases, includes both the elastic stiffness, due to the material properties and member configuration, as well as geometric or initial stress stiffness due to pre-loads. Accurate prediction of the natural frequencies and mode shapes is essential for determining the adequacy of components, and for designing a controls system.

The finite element method is normally used to perform this analysis. However, a phenomenon known as "grounding" or false stiffening, occurs when the geometric stiffness matrix is used. When a pre-loaded model with free/free boundary conditions is analyzed, it behaves as if it is restrained internally. Thus, it is unable to rotate as a rigid body. Instead, erroneous "pseudo-forces" develop during rigid body motion. Free vibration analysis also yields an erroneous (non-zero) natural frequency associated with rigid body rotation. Bosela *et al.* [1-3] have examined the grounding phenomenon for a pre-loaded beam, and determined that it is caused by a force imbalance during rigid body rotation, and is typical of beam geometric stiffness matrices formulated by others, even those which include higher order effects. By utilizing a directed force premise, and extending to a global model the natural mode approach used by Argyris and Symeonidis [4] for developing load correction factors for non-conservative forces, a pre-loaded beam geometric stiffness matrix with full rigid body capabilities was developed and tested [3, 5].

This paper has the following objectives:

- (1) Examine the grounding phenomenon as it relates to pre-loaded membrane elements.
- (2) Develop a pre-loaded membrane element with full rigid body capabilities by following the directed force approach used successfully in developing the pre-loaded beam element.

MEMBRANE ELEMENTS

Although various membrane elements are used in commercial finite element programs, most are not readily available in explicit form. One which is stated explicitly by Yang [6] is the four-node rectangular element in Fig. 1, which has either 12 or 16 degrees of freedom (DOF). The degrees of freedom numbered

as 13, 14, 15 and 16, correspond to second-order twist terms such as $\partial^2 w / \partial x \partial y$. This element is obtained by combining the shape functions for the elementary beam element in both the x and y directions.

The geometric, or initial stress stiffness matrix $[K_g]$ for this plate element when the distributed load is in the x -direction only is

$$[K_g] = \begin{bmatrix} A_1 & A_2 & A_3 & A_4 & A_5 & A_6 & A_7 & A_8 & A_9 & A_{10} & A_{11} & A_{12} & A_{13} & A_{14} & A_{15} & A_{16} \\ B_1 & B_2 & B_3 & B_4 & B_5 & B_6 & B_7 & B_8 & B_9 & B_{10} & B_{11} & B_{12} & B_{13} & B_{14} & B_{15} & B_{16} \\ C_1 & C_2 & C_3 & C_4 & C_5 & C_6 & C_7 & C_8 & C_9 & C_{10} & C_{11} & C_{12} & C_{13} & C_{14} & C_{15} & C_{16} \\ D_1 & D_2 & D_3 & D_4 & D_5 & D_6 & D_7 & D_8 & D_9 & D_{10} & D_{11} & D_{12} & D_{13} & D_{14} & D_{15} & D_{16} \\ E_1 & E_2 & E_3 & E_4 & E_5 & E_6 & E_7 & E_8 & E_9 & E_{10} & E_{11} & E_{12} & E_{13} & E_{14} & E_{15} & E_{16} \\ F_1 & F_2 & F_3 & F_4 & F_5 & F_6 & F_7 & F_8 & F_9 & F_{10} & F_{11} & F_{12} & F_{13} & F_{14} & F_{15} & F_{16} \\ G_1 & G_2 & G_3 & G_4 & G_5 & G_6 & G_7 & G_8 & G_9 & G_{10} & G_{11} & G_{12} & G_{13} & G_{14} & G_{15} & G_{16} \\ H_1 & H_2 & H_3 & H_4 & H_5 & H_6 & H_7 & H_8 & H_9 & H_{10} & H_{11} & H_{12} & H_{13} & H_{14} & H_{15} & H_{16} \\ I_1 & I_2 & I_3 & I_4 & I_5 & I_6 & I_7 & I_8 & I_9 & I_{10} & I_{11} & I_{12} & I_{13} & I_{14} & I_{15} & I_{16} \\ J_1 & J_2 & J_3 & J_4 & J_5 & J_6 & J_7 & J_8 & J_9 & J_{10} & J_{11} & J_{12} & J_{13} & J_{14} & J_{15} & J_{16} \\ K_1 & K_2 & K_3 & K_4 & K_5 & K_6 & K_7 & K_8 & K_9 & K_{10} & K_{11} & K_{12} & K_{13} & K_{14} & K_{15} & K_{16} \\ L_1 & L_2 & L_3 & L_4 & L_5 & L_6 & L_7 & L_8 & L_9 & L_{10} & L_{11} & L_{12} & L_{13} & L_{14} & L_{15} & L_{16} \\ M_1 & M_2 & M_3 & M_4 & M_5 & M_6 & M_7 & M_8 & M_9 & M_{10} & M_{11} & M_{12} & M_{13} & M_{14} & M_{15} & M_{16} \\ N_1 & N_2 & N_3 & N_4 & N_5 & N_6 & N_7 & N_8 & N_9 & N_{10} & N_{11} & N_{12} & N_{13} & N_{14} & N_{15} & N_{16} \\ P_1 & P_2 & P_3 & P_4 & P_5 & P_6 & P_7 & P_8 & P_9 & P_{10} & P_{11} & P_{12} & P_{13} & P_{14} & P_{15} & P_{16} \\ Q_1 & Q_2 & Q_3 & Q_4 & Q_5 & Q_6 & Q_7 & Q_8 & Q_9 & Q_{10} & Q_{11} & Q_{12} & Q_{13} & Q_{14} & Q_{15} & Q_{16} \end{bmatrix}, \quad (1)$$

$$\begin{aligned} A_1 &= B_2 = C_3 = D_4 = \frac{78N_x b}{175a} & A_2 &= B_1 = C_4 = D_3 = -\frac{78N_x b}{175a} \\ A_4 &= B_3 = C_2 = D_1 = \frac{27N_x b}{175a} & A_3 &= B_4 = C_1 = D_2 = -\frac{27N_x b}{175a} \\ A_5 &= A_6 = D_7 = D_8 = \frac{13N_x b}{350} & B_5 &= B_6 = C_7 = C_8 = -\frac{13N_x b}{350} \\ A_7 &= A_8 = D_5 = D_6 = \frac{9N_x b}{700} & B_7 &= B_8 = C_5 = C_6 = -\frac{9N_x b}{700} \\ A_9 &= B_{10} = C_{12} = D_{11} = \frac{11N_x b^2}{175a} & A_{10} &= B_9 = C_{11} = D_{12} = -\frac{11N_x b^2}{175a} \\ A_{11} &= B_{12} = C_{10} = D_9 = \frac{13N_x b^2}{350a} & A_{12} &= B_{11} = C_9 = D_{10} = -\frac{13N_x b^2}{350a} \\ A_{13} &= A_{14} = C_{15} = C_{16} = \frac{11N_x b^2}{2100} & B_{13} &= B_{14} = D_{15} = D_{16} = -\frac{11N_x b^2}{2100} \\ B_{15} &= B_{16} = D_{13} = D_{14} = \frac{13N_x b^2}{4200} & A_{15} &= A_{16} = C_{13} = C_{14} = -\frac{13N_x b^2}{4200} \\ E_1 &= F_1 = G_4 = H_4 = \frac{13N_x b}{350} & E_2 &= F_2 = G_3 = H_3 = -\frac{13N_x b}{350} \end{aligned}$$

Fig. 1.(a) Four-node rectangular plate element with 16 DOF. (b) In-plane normal and shear forces on quadrilateral membrane element.

$$\begin{aligned}
 E_4 = F_4 = G_1 = H_1 &= \frac{9N_x b}{700} & E_3 = F_3 = G_2 = H_2 &= -\frac{9N_x b}{700} \\
 E_5 = F_6 = G_7 = H_8 &= \frac{26N_x ab}{525} & E_6 = F_5 = G_8 = H_7 &= -\frac{13N_x ab}{1050} \\
 E_7 = F_8 = G_5 = H_6 &= -\frac{3N_x ab}{700} & E_8 = F_7 = G_6 = H_5 &= \frac{3N_x ab}{175} \\
 E_9 = F_9 = G_{11} = H_{11} &= \frac{11N_x b^2}{2100} & E_{10} = F_{10} = G_{12} = H_{12} &= -\frac{11N_x b^2}{2100} \\
 E_{11} = F_{11} = G_9 = H_9 &= \frac{13N_x b^2}{4200} & E_{12} = F_{12} = G_{10} = H_{10} &= -\frac{13N_x b^2}{4200} \\
 E_{13} = F_{14} &= \frac{11N_x ab^2}{1575} & G_{15} = H_{16} &= -\frac{11N_x ab^2}{1575} \\
 G_{16} = H_{15} &= \frac{11N_x ab^2}{6300} & E_{14} = F_{13} &= -\frac{11N_x ab^2}{6300} \\
 E_{15} = F_{16} &= \frac{13N_x ab^2}{12600} & G_{13} = H_{14} &= -\frac{13N_x ab^2}{12600} \\
 G_{14} = H_{13} &= \frac{13N_x ab^2}{3150} & E_{16} = F_{15} &= -\frac{13N_x ab^2}{3150} \\
 I_1 = J_2 = K_4 = L_3 &= \frac{11N_x b^2}{175a} & I_2 = J_1 = K_3 = L_4 &= -\frac{11N_x b^2}{175a} \\
 I_4 = J_3 = K_1 = L_2 &= \frac{13N_x b^2}{350a} & I_3 = J_4 = K_2 = L_1 &= -\frac{13N_x b^2}{350a} \\
 I_5 = I_6 = K_7 = K_8 &= \frac{11N_x b^2}{2100} & J_5 = J_6 = L_7 = L_8 &= -\frac{11N_x b^2}{2100}
 \end{aligned}$$

$$\begin{aligned}
I_7 = I_8 = K_5 = K_6 &= \frac{13N_x b^2}{4200} & J_7 = J_8 = L_5 = L_6 &= -\frac{13N_x b^2}{4200} \\
I_9 = J_{10} = K_{11} = L_{12} &= \frac{2N_x b^3}{175a} & I_{10} = K_{12} = L_{11} = J_9 &= -\frac{2N_x b^3}{175a} \\
I_{11} = J_{12} = K_9 = L_{10} &= \frac{3N_x b^3}{350a} & I_{12} = J_{11} = K_{10} = L_9 &= -\frac{3N_x b^3}{350a} \\
I_{13} = I_{14} = L_{15} = L_{16} = M_9 = N_9 = Q_{12} = P_{12} &= \frac{N_x b^3}{1050} \\
J_{13} = J_{14} = K_{15} = K_{16} = M_{10} = P_{11} = Q_{11} &= -\frac{N_x b^3}{1050} \\
J_{15} = J_{16} = K_{13} = K_{14} = M_{11} = N_{11} = P_{10} = Q_{10} &= \frac{N_x b^3}{1400} \\
I_{15} = I_{16} = L_{13} = L_{14} = M_{12} = N_{12} = P_9 = Q_9 &= -\frac{N_x b^3}{1400} \\
M_1 = N_1 = P_3 = Q_3 &= \frac{11N_x b^2}{2100} & M_2 = N_2 = P_4 = Q_4 &= -\frac{11N_x b^2}{2100} \\
M_4 = N_4 = P_2 = Q_2 &= \frac{13N_x b^2}{4200} & M_3 = N_3 = P_1 = Q_1 &= -\frac{13N_x b^2}{4200} \\
M_5 = N_6 &= \frac{11N_x a b^2}{1575} & M_6 = N_5 &= -\frac{11N_x a b^2}{6300} \\
M_8 = N_7 &= \frac{13N_x a b^2}{3150} & M_7 = N_8 &= -\frac{13N_x a b^2}{12600} \\
M_{13} = N_{14} = P_{15} = Q_{16} &= \frac{2N_x a b^3}{1575} & M_{14} = N_{13} = P_{16} = Q_{15} &= -\frac{N_x a b^3}{3150} \\
M_{15} = N_{16} = P_{13} = Q_{14} &= \frac{N_x a b^3}{4200} & M_{16} = N_{15} = P_{14} = Q_{13} &= -\frac{N_x a b^3}{1050} \\
P_5 = Q_6 &= \frac{13N_x a b^2}{12600} & N_{10} &= -\frac{N_x b^3}{1050} & P_6 = Q_5 &= -\frac{13N_x a b^2}{3150} \\
P_8 = Q_7 &= \frac{11N_x a b^2}{6300} & P_7 = Q_8 &= -\frac{11N_x a b^2}{1575}.
\end{aligned} \tag{2}$$

In order to solve for the natural frequencies, the corresponding four-node quadrilateral mass matrix developed by Yang was also used. The coefficients of the mass matrix are determined by using the

equation

$$\mathbf{M}_{ij} = \rho h \int_0^b \int_0^a f_i(x, y) f_j(x, y) \, dx \, dy. \tag{3}$$

$$[M] = \rho abh$$

SYMMETRIC											
169	129	169	13a ²	13a ²	13a ³	13b ²	13b ²	13b ²	13b ³	a ² b ²	a ² b ²
1225	1225	1225	3675	3675	3675	3675	3675	3675	3675	11025	11025
2450	2450	2450	9000	9000	9000	9000	9000	9000	9000	14700	14700
81	117	117	33a	33a	3a ³	3b ³	3b ³	3b ³	3b ³	a ² b ²	a ² b ²
4900	4900	4900	169a	169a	2450	2450	2450	2450	2450	14700	14700
117	81	81	1225	1225	9800	9800	9800	9800	9800	19600	19600
2450	2450	2450	33a	33a	143a	143a	143a	143a	143a	14700	14700
143a	169a	169a	4900	4900	7350	7350	7350	7350	7350	19600	19600
7350	14700	14700	3675	3675	14700	14700	14700	14700	14700	14700	14700
-169a	-143a	-33a	-13a ²	-13a ²	-9a ³	-143ab	-143ab	-143ab	-143ab	-a ² b ²	-a ² b ²
14700	7350	4900	9000	9000	2450	2450	2450	2450	2450	14700	14700
-39a	-33a	-143a	-9a ²	-9a ²	9800	9800	9800	9800	9800	19600	19600
9800	4900	7350	14700	14700	143a	143a	143a	143a	143a	14700	14700
33a	39a	169a	143a	143a	3a ³	3a ³	3a ³	3a ³	3a ³	14700	14700
4900	9800	14700	2450	2450	9800	9800	9800	9800	9800	19600	19600
143b	33b	39b	121ab	121ab	-143ab	-143ab	-143ab	-143ab	-143ab	-a ² b ²	-a ² b ²
7350	4900	9800	44100	44100	88200	88200	88200	88200	88200	14700	14700
36b	143b	169b	143ab	143ab	-121ab	-121ab	-121ab	-121ab	-121ab	14700	14700
4900	7350	14700	88200	88200	44100	44100	44100	44100	44100	19600	19600
-39b	-169b	-143b	-169ab	-169ab	143ab	143ab	143ab	143ab	143ab	14700	14700
9800	14700	7350	176400	176400	88200	88200	88200	88200	88200	14700	14700
-169b	-39b	-33b	-143ab	-143ab	169ab	169ab	169ab	169ab	169ab	14700	14700
14700	4900	7350	88200	88200	11a ² b	11a ² b	11a ² b	11a ² b	11a ² b	14700	14700
121ab	143ab	169ab	11a ² b	11a ² b	-13a ² b	-13a ² b	-13a ² b	-13a ² b	-13a ² b	14700	14700
44100	88200	176400	22050	22050	58800	58800	58800	58800	58800	14700	14700
-143ab	-121ab	-143ab	-11a ² b	-11a ² b	13a ² b	13a ² b	13a ² b	13a ² b	13a ² b	14700	14700
88200	44100	88200	29400	29400	44100	44100	44100	44100	44100	14700	14700
169ab	143ab	121ab	13a ² b	13a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	14700	14700
176400	88200	44100	58800	58800	22050	22050	22050	22050	22050	14700	14700
-143ab	-169ab	-143ab	-13a ² b	-13a ² b	11a ² b	11a ² b	11a ² b	11a ² b	11a ² b	14700	14700
88200	44100	88200	22050	22050	44100	44100	44100	44100	44100	14700	14700
169ab	143ab	121ab	13a ² b	13a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	14700	14700
176400	88200	44100	58800	58800	22050	22050	22050	22050	22050	14700	14700
-143ab	-169ab	-143ab	-13a ² b	-13a ² b	11a ² b	11a ² b	11a ² b	11a ² b	11a ² b	14700	14700
88200	44100	88200	22050	22050	44100	44100	44100	44100	44100	14700	14700
169ab	143ab	121ab	13a ² b	13a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	14700	14700
176400	88200	44100	58800	58800	22050	22050	22050	22050	22050	14700	14700
-143ab	-169ab	-143ab	-13a ² b	-13a ² b	11a ² b	11a ² b	11a ² b	11a ² b	11a ² b	14700	14700
88200	44100	88200	22050	22050	44100	44100	44100	44100	44100	14700	14700
169ab	143ab	121ab	13a ² b	13a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	14700	14700
176400	88200	44100	58800	58800	22050	22050	22050	22050	22050	14700	14700
-143ab	-169ab	-143ab	-13a ² b	-13a ² b	11a ² b	11a ² b	11a ² b	11a ² b	11a ² b	14700	14700
88200	44100	88200	22050	22050	44100	44100	44100	44100	44100	14700	14700
169ab	143ab	121ab	13a ² b	13a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	-11a ² b	14700	14700
176400	88200	44100	58800	58800	22050	22050	22050	22050	22050	14700	14700
 

$$\frac{a^2b^2}{11025}$$

GROUNDING OF MEMBRANE ELEMENTS

Suppose one considers a free/free model with two 12 DOF elements, and a uniform tensile load applied in the x -direction only, as shown in Fig. 2. That element should possess five rigid body modes: (1) translation in the y -direction; (2) rigid body rotation about the x -axis; (3) rotation of the edge line between nodes 1, 2 and 5; (4) rotation of the edge lines between nodes 4, 3 and 6; (5) rigid body rotation about the y -axis. It should be noted that (2) and (4) only occur because for the example problem, there is no tension in the y -direction, and we are neglecting elastic stiffness effects.

In matrix form, assembling $[Kg]$ and multiplying a matrix of these rigid body modes yields

$$[Kg] \cdot \begin{bmatrix} 1 & -1 & 0 & 0 & -1 \\ 1 & -1 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & 0 \\ 1 & 1 & 0 & 0 & -1 \\ 0 & 0 & 0 & 0 & \frac{1}{a} \\ 0 & 0 & 0 & 0 & \frac{1}{a} \\ 0 & 0 & 0 & 0 & \frac{1}{a} \\ 0 & 0 & 0 & 0 & \frac{1}{a} \\ 0 & \frac{2}{b} & 1 & 0 & 0 \\ 0 & \frac{2}{b} & 1 & 0 & 0 \\ 0 & \frac{2}{b} & 0 & 1 & 0 \\ 0 & \frac{2}{b} & 0 & 1 & 0 \\ 1 & -1 & 0 & 0 & 1 \\ 1 & 1 & 0 & 0 & 1 \\ 0 & 0 & 0 & 0 & \frac{1}{a} \\ 0 & 0 & 0 & 0 & \frac{1}{a} \\ 0 & \frac{2}{b} & 1 & 0 & 0 \\ 0 & \frac{2}{b} & 0 & 1 & 0 \end{bmatrix} = \begin{bmatrix} 0 & 0 & 0 & 0 & -\frac{Nb}{2a} \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -\frac{Nb}{2a} \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -\frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -\frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & \frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & \frac{Nb}{2a} \\ 0 & 0 & 0 & 0 & \frac{Nb}{2a} \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & \frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & \frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & -\frac{Nb^2}{12a} \end{bmatrix} \quad (5)$$

to rigid body rotation about the y -axis, was not present. Instead, pseudo-forces developed in degree of freedoms 1, 4, 9, 12, 13, 14, 17 and 18. The pseudo-forces in degrees of freedom 1, 4, 13 and 14 correspond to the forces required to keep the rotated model in equilibrium, which is consistent with the behavior of a pre-loaded beam element [2]. Hence, the procedure used successfully for the pre-loaded beam element [3] will be adapted.

The pseudo-moments developed in degrees of freedom 9, 12, 17 and 18 did not occur with rotation of the pre-loaded beam element. It should be noted, however, that the form resembles a fixed-end moment caused by a distributed load.

Examining the right hand side of eqn (5) reveals that rigid body modes 1-4 are present in the global $[Kg]$. However, mode #5, which corresponds

DIRECTED-FORCE APPROACH

Consider Argyris's methodology [4] for the directed force problem. Let $\phi \cong (u_4 - u_{18})/2a$ or

Combining $[Kg] + [K^{DFC}]$ and multiplying by the rigid body mode matrix yields

$$[[Kg] + [K^{DFC}]] \cdot [\text{Rigid Body Modes}] = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & -\frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & \frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & \frac{Nb^2}{12a} \\ 0 & 0 & 0 & 0 & -\frac{Nb^2}{12a} \end{bmatrix} \quad (8)$$

Note that the pseudo-force terms associated with degrees of freedom 1, 4, 13 and 14 have disappeared, but the pseudo-moment terms associated with degrees of freedom 9, 12, 17 and 18 remain.

Once again, consider a rotation ϕ about the y -axis, and let $\phi = (u_{13} + u_{14} - u_1 - u_4)/4a$. We have considered the equivalent concentrated vertical loads at the nodes due to the rotation in the determination of $[K^{DFC}]$. However, this vertical component is really based on a distributed load. In order to replace it with concentrated loads at the node points, we must also include fixed-end moments. The load vector for the fixed end moments caused by the vertical distributed loads would be

$$\mathbf{R}_{FEM} = \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & \frac{Nb^2}{12} \times \sin \phi & 0 & 0 & -\frac{Nb^2}{12} \sin \phi & 0 & 0 & 0 & 0 \\ & & & & & & & & & & & & & & & & -\frac{Nb^2}{12} \sin \phi & \frac{nB^2}{12} \sin \phi \end{bmatrix}. \quad (9)$$

Taking $\frac{\partial \mathbf{R}_i^{FEM}}{\partial v_i}$, assuming small angles and enforcing symmetry yields

(10)

Thus, the all pseudo-forces and pseudo-moments have been eliminated.

(11)

In order to determine the effect of the correction factors, a comparison of the first 12 natural frequencies of vibration was performed for the two element model. The results are included in Table 1.

Frequency	Yang's [Kg] 16 DOF	Yang's [Kg] 24 DOF	Corrected 16 DOF	Corrected 24 DOF
1	0	0	0	0
2	0	0	0	0
3	0	0	0	0
4	0	0	0	0
5	103.2	0	0	0.0152
6	103.2	0	103.2	103.2
7	118.0	0	118.0	103.2
8	118.0	0	206.4	174.7
9	206.4	0	206.4	206.4
10	206.4	0	206.4	206.4
11	206.4	0	206.4	206.4
12	206.4	0	268.3	206.4

As the table indicates, the missing rigid body mode (mode # 5, frequency = 0), was obtained when the total directed force correction factors were added to Yang's [Kg].

SUMMARY

Based upon this investigation, the following conclusions can be made:

(1) Pre-loaded membrane elements exhibit the same "grounding" problems associated with pre-loaded beam elements. In other words, an internal grounding, or false stiffening, occurs when they are subjected to a rigid body rotation, which generates erroneous pseudo-forces.

(2) In addition to the pseudo-forces, erroneous pseudo-moments also develop during rigid body rotation.

(3) An erroneous non-zero frequency develops during rigid body rotation, instead of the required zero frequency associated with a rigid body mode.

(4) Using a directed force premise, and extending the Argyris approach for developing correction factors for non-conservative forces to the global level,

the pseudo-forces were eliminated, but the pseudo-moments still remained.

(5) By considering the fixed-end moments associated with the distributed load, and similarly developing correction factors, the pseudo-moments were eliminated, and the missing zero frequency associated with rigid body rotation were obtained.

(6) Future work should include comparison of results for larger models and with test results.

REFERENCES

1. P. Bosela, F. Shaker and D. Fertis, Dynamic analysis of space-related linear and non-linear structures. *Comput. Struct.* **44**, 1145–1148 (1992).
2. P. Bosela, D. Fertis and F. Shaker, Grounding of space structures. *Comput. Struct.* **45**, 143–153 (1992).
3. P. Bosela, D. Fertis and F. Shaker, A new pre-loaded beam geometric stiffness matrix with full rigid body capabilities. *Comput. Struct.* **45**, 155–163 (1992).
4. J. Argyris and Sp. Symeonidis, Nonlinear finite element analysis of elastic systems under non-conservative loading-natural formulation. Part 1. Quasistatic problems. *Comput. Meth. appl. Mech. Engng* **26**, 75–123 (1981).
5. D. Fertis, *Mechanical and Structural Vibrations*. Wiley, New York (1995).
6. T. Yang, *Finite Element Structural Analysis*. Prentice-Hall, Englewood Cliffs, NJ (1986).