### **Cleveland State University**

## EngagedScholarship@CSU

**Undergraduate Research Posters 2015** 

**Undergraduate Research Posters** 

2015

## Integrating an Android Device into Embedded Computer Systems

Eric Payne Cleveland State University

Follow this and additional works at: https://engagedscholarship.csuohio.edu/u\_poster\_2015



Part of the Engineering Commons

How does access to this work benefit you? Let us know!

#### **Recommended Citation**

Payne, Eric, "Integrating an Android Device into Embedded Computer Systems" (2015). Undergraduate Research Posters 2015. 59.

https://engagedscholarship.csuohio.edu/u\_poster\_2015/59

This Book is brought to you for free and open access by the Undergraduate Research Posters at EngagedScholarship@CSU. It has been accepted for inclusion in Undergraduate Research Posters 2015 by an authorized administrator of EngagedScholarship@CSU. For more information, please contact library.es@csuohio.edu.



# Integrating an Android Device into Embedded Computer Systems

Washkewicz College of Engineering

**Student Researcher:** Eric Payne

**Faculty Advisor:** Pong Chu

## **Abstract**

An embedded system is a computer system designed to perform a specific set of tasks such as a GPS device or a digital camera. An embedded system is composed of three major parts: a processor (CPU), input devices, and output devices. The input devices are peripherals to take user command (switches and keypad) and sensors to measure environmental conditions (barometer and accelerometer). The output devices are actuators that generate light and sound (LED display and amplified speaker) and moving parts (servo motor).

An important step in prototyping an embedded system is to design the input subsystem. It is traditionally done by selecting input modules and then developing hardware and software interfaces for each individual module. The undergraduate summer research is to use an inexpensive, entry-level, Android phone as a universal programmable sensor module. It provides a single unified interface and can be configured to replace a dozen commonly used input devices.